












## Stingray

Stingray frame measurement (mm)		1	2
	(G) Overall width, frame	590 (23")	590 (23")
	(H1) Length with turnable front wheels	740 (28¾") 840 (32¾")	740 (28¾") 840 (32¾")
	(I) Overall height, push brace 15°	1000,1030,1060 (39",40",41¼")	1000,1030,1060 (39",40",41¼")
	(D) Footrest to seat distance	140-450 (5½-17½")	140-450 (5½-17½")
	Leg to seat surface angling	-30° -> 30°	-30° -> 30°
	(E) Seat surface height at front edge	520 (20¼")	520 (20¼")
	Seat plane angle	45°	45°
	Minimum turning radius	1020 (39¾")	1020 (39¾")
	Folded length	900 (35")	900 (35")
	Folded height	490 (19")	490 (19")
	Total mass	13.5 kg (29,5 lb)	13.5 kg (29.5 lb)
	Max. load, frame	40 kg (88 lb)	40 kg (88 lb)
	Max. user weight, seat and frame	40 kg (88 lb)	40 kg (88 lb)
	Max load at transportation	40 kg (88 lb)	40 kg (88 lb)
	Static stability (Sideways, forward & rearward)	10°	10°



Stingray seat measurement (mm)		1	2
	(A) Effective seat width	300 (11¾")	350 (13¾")
	(B) Effective seat depth	180-300 (7-11¾")	250-400 (9¾-15½")
	(C1) Backrest height	410-550 (16-21½")	500-650 (19½-25¼")
	Seat width, folded	420 (16½")	475 (18½")
	Seat length, folded	575 (22½")	575 (22½")
	Seat height, folded	285 (11")	305 (12")
	Footrest to seat distance	140-450 (5½-17½")	140-450 (5½-17½")
	Backrest angle	170°	170°
	Total mass	5.5 kg (12 lb)	6.5 kg (14.5 lb)
	Max load	40 kg (88 lb)	40 kg (88 lb)
	Max. user load at transportation	40 kg (88 lb)	40 kg (88 lb)